

Mobil 1 0W-40

Most Advanced Performance Synthetic Engine Oil

Product Description

Mobil 1 0W-40 is the most advanced performance synthetic engine oil designed to provide ultimate cleaning power, wear protection and overall performance. Mobil 1 0W-40, European Car Formula (NA) or Protection Formula (EU), exceeds the requirements of the leading industry and car manufacturers' standards required for newer modern gasoline and diesel powered automobile engines. The Mobil 1 Technology is race proven and the choice of NASCAR racing. Mobil 1 0W-40 is perfect for all types of vehicles anywhere in the world and has the performance reserve to protect when conventional engine oils cannot. It is the first choice at the factory for the some of the world's finest performance vehicles: Mercedes-Benz AMG, Porsche, and Aston Martin.

Features & Benefits

Mobil 1 0W-40 is made with a patented proprietary blend of ultra high performance synthetic basestocks fortified with Supersyn Antiwear Technology, the most advanced additive system available today. Mobil 1 0W-40's wide viscosity range provides unsurpassed levels of protection, fuel savings and the best overall smooth driving experience. Mobil 1 0W-40 keeps engines starting in Arctic extreme cold and cleans deposits, sludge and varnish often formed in high temperature operating conditions. Exceeding all of the global industry standards and the major leading builder requirements is the cornerstone of the performance reserve that lets Mobil 1 0W-40 keep performing well after conventional oils cannot. Key features and benefits include:

Features	Advantages and Potential Benefits
Active cleaning agents	Prevents deposits and sludge build-up to enable long and clean engine life
Outstanding thermal and oxidation stability	Reduces oil ageing allowing extended drain interval protection
Low oil consumption	Less hydrocarbon pollution
Enhanced frictional properties	Greater fuel economy
Excellent low temperature capabilities	Quick cold weather starting and ultra fast protection Extended engine and electrical system life
High Viscosity Index and Supersyn Antiwear Technology	Excellent overall lubrication and wear protection performance for all driving styles and conditions

Applications

Mobil 1 0W-40 is recommended for all types of modern vehicles, especially high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- Mobil 1 0W-40 is especially suitable for extreme conditions, where conventional oil often can't perform.
- Mobil 1 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Specifications & Approvals

Mobil 1 0W-40 meets or exceeds the following industry specifications:

ACEA	A3,B3,B4
API	SL,SJ,EC,CF
ILSAC	GF3

Mobil 1 0W-40 has the following builder approvals:

BMW	LL-01
Daimler Chrysler	229.3/229.5
Opel Long Life Service Fill	GM-LL-A-025
Opel Diesel Service Fill	GM-LL-B-025
Porsche	Approved
Volkswagen	502.00/505.00,503.01

Typical Properties

Filling	RN 4677 AAAD
Mobil 1 0W-40	
SAE Grade	0W-40
Viscosity, ASTM D 445	
cSt @ 40° C	80
cSt @ 100° C	14.3
Viscosity Index, ASTM D 2270	187
Sulfated Ash, wt%, ASTM D 874	1.2
HTHS Viscosity, mPa·s @ 150° C, ASTM D 4683	3.6
Pour Point, °C, ASTM D 97	-54
Flash Point, °C, ASTM D 92	236
Density @15° C kg/l, ASTM D 4052	0.855

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil 1 with Supersyn are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

